电机特性表 Specifications of Motor

电机类型	电机型号		功率	频率	电压	电流	起动特性	额定		起动电容		齿轮型号	
	Motor Model		Power	Frequency	Voltage	Current	Starting Characteristics	Output	Speed	Capacitor	Withstand Voltage	Bearing	Intermediate Gear
								(g.cm)	(r.p.m)	(μF)	(V)		
	6RK120A-A	6RK120GU-A	120	50	110	2.40	9500	9000	1300	35	250	6GU-K	6GM10X
				60	110	2.20	7900	7550	1550	30			
	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]			
可逆型马达 Reversible motor	[illegible]A-C	6RK120GU-C	120	60	220	1.10	7900	7550	1550	7	500	6GU-K	6GM10X
	6RK140[illegible]A	6RK140GU-A	140	50	110	2.80	11000	10500	1300	40	250	6GU-K	6GM10X
				60	110	2.60	9500	9000	1550	30			
	6RK140[illegible]	6RK140GU-C	140	50	220	1.40	11000	10500	1300	10	500	6GU-K	6GM10X
				60	220	1.20	9500	9000	1550	8			

外形尺寸 Outline Dimension

型号 Model	减速比 Reduction Ratio	L1 (mm)	L2 (mm)	L3 (mm)	h (mm)
6RK120[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]

齿轮减速电机, Gear Motor

键KEY

接线图 Terminal Table

[illegible]					
[illegible]	50Hz	3	5	7.5	10